SYSTEM UTILIZATION MONTHLY REPORT

for the month ending

February 2022

http://www.tccustomerexpress.com/2885.html

Published date:
April 14th, 2022

Highlights This Month:

- NGTL Segment map (page 21 of this report) has been updated

NOVA Gas Transmission Ltd.

TC Energy

TABLE OF CONTENTS

Utilization reports are posted approximately six weeks after the end of the reported month.

If you have any questions on the content of this report, contact Winston Cao at (403) 920-5315 or winston_cao@tcenergy.com.

TC Energy

FIRM TRANSPORTATION SERVICE[1] CONTRACT UTILIZATION[3]

By NGTL Pipeline Segments

February 2022

		Delivery		Receipt	
Segment	Contract	Utilization	Feb CD (TJ/d)	Utilization	Feb CD (MMcf/d)
UPRM	FT	0%	0.0	95%	79
	FT + IT[2]	0%		95%	
PRLL	FT	66%	29.3	78%	233
	FT + IT	109%		85%	
NWML	FT	0%	0.0	90%	144
	FT + IT	0%		92%	
GRDL	FT	0%	0.0	72%	4,986
	FT + IT	0%		73%	
WAEX	FT	49%	21.1	62%	1,156
	FT + IT	72%		63%	
JUDY	FT	72%	19.6	86%	24
	FT + IT	87%		112%	
GPML	FT	72%	221.2	73%	5,382
	FT + IT	111%		75%	
CENT	FT	53%	6.6	56%	2,649
	FT + IT	62%		57%	
LPOL	FT	52%	312.0	66%	1,109
	FT + IT	63%		71%	
WGAT	FT	87%	4,412.7	90%	207
	FT + IT	89%		107%	
ALEG	FT	65%	374.1	94%	437
	FT + IT	68%		125%	
SLAT	FT	53%	164.9	98%	70
	FT + IT	53%		144%	
MLAT	FT	97%	274.5	97%	83
	FT + IT	100%		118%	
BLEG	FT	42%	112.4	99%	384
	FT + IT	46%		118%	
EGAT	FT	97%	4,863.6	99%	4
	FT + IT	108%		262%	
MRTN	FT	68%	26.1	82%	37
	FT + IT	73%		109%	
LIEG	FT	83%	2,077.1	82%	16
	FT + IT	84%		105%	
KIRB	FT	92%	1,695.6	93%	5
	FT + IT	93%		217%	
SMHI	FT	0%	0.0	0%	0
	FT + IT	0%		0%	
REDL	FT	40%	17.9	63%	10
	FT + IT	40%		103%	
COLD	FT	71%	291.5	65%	4
	FT + IT	74%		223%	
EDM	FT	62%	1,851.3	97%	19
	FT + IT	63%		201%	
NLAT	FT	45%	291.8	95%	81
	FT + IT	45%		121%	
WAIN	FT	58%	0.3	81%	2
	FT + IT	154%		136%	
ELAT	FT	87%	307.5	92%	61
	FT + IT	87%		136%	
TOTAL SYSTEM	FT	84%	17,371.1	71%	17,183
	FT + IT	89%		75%	

*NOTE:

1. FT includes all receipt and delivery Firm Transportation Services.
2. IT includes receipt and delivery Interruptible Services.
3. Utilization data is based on billed monthly volumes. Percent utilization calculated as FT and FT + IT billed volumes divided by applicable receipt or delivery Contract level.

TC Energy

DESIGN CAPABILITY UTILIZATION
UPPER PEACE RIVER





% Design Capability Utilization						
Average Flow/	Sep	Oct	Nov	Dec	Jan	Feb
	26%	26%	25%	23%	23%	24%

TC Energy

DESIGN CAPABILITY UTILIZATION
UPPER and CENTRAL PEACE RIVER





% Design Capability Utilization						
Average Flow/	Sep	Oct	Nov	Dec	Jan	Feb
	89%	85%	84%	83%	79%	81%

TC Energy

DESIGN CAPABILITY UTILIZATION
PEACE RIVER DESIGN
(Upper, Central and Lower Peace River)





% Design Capability Utilization						
Average Flow/	Sep	Oct	Nov	Dec	Jan	Feb
	84%	85%	85%	85%	84%	85%

TC Energy

DESIGN CAPABILITY UTILIZATION
UPSTREAM JAMES RIVER
(Edson Mainline, Peace River Design and Marten Hills)





% Design Capability Utilization						
Average Flow/	Sep	Oct	Nov	Dec	Jan	Feb
	87%	90%	91%	91%	90%	92%

TC Energy

DESIGN CAPABILITY UTILIZATION
EASTERN ALBERTA MAINLINE
(James River to Princess)



% Design Capability Utilization						
Average Flow/	Sep	Oct	Nov	Dec	Jan	Feb
	103%	110%	105%	98%	105%	106%

TC Energy

DESIGN CAPABILITY UTILIZATION
WESTERN ALBERTA MAINLINE
(Alberta/B.C. and Alberta/Montana Borders)



% Design Capability Utilization						
Average	Sep	Oct	Nov	Dec	Jan	Feb
Flow/	82%	86%	87%	96%	98%	97%

TC Energy

DESIGN CAPABILITY UTILIZATION
RIMBEY-NEVIS – FLOW WITHIN





% Design Capability Utilization						
Average Flow/	Sep	Oct	Nov	Dec	Jan	Feb
	60%	76%	66%	73%	77%	73%

TC Energy

DESIGN CAPABILITY UTILIZATION
SOUTH and ALDERSON – FLOW WITHIN





% Design Capability Utilization						
Average	Sep	Oct	Nov	Dec	Jan	Feb
Flow/	45%	70%	54%	79%	72%	67%

TC Energy

DESIGN CAPABILITY UTILIZATION
MEDICINE HAT – FLOW WITHIN





% Design Capability Utilization						
Average Flow/	Sep	Oct	Nov	Dec	Jan	Feb
	70%	75%	70%	77%	80%	80%

TC Energy

DESIGN CAPABILITY UTILIZATION
EASTERN ALBERTA MAINLINE
(Princess to Empress / McNeill)



% Design Capability Utilization						
Average Flow/	Sep	Oct	Nov	Dec	Jan	Feb
	85%	86%	99%	97%	103%	108%

TC Energy

DESIGN CAPABILITY UTILIZATION
FT. McMURRAY AREA – FLOW WITHIN





% Design Capability Utilization						
Average Flow/	Sep	Oct	Nov	Dec	Jan	Feb
	92%	100%	85%	88%	93%	93%

TC Energy

DESIGN CAPABILITY UTILIZATION
KIRBY AREA – FLOW WITHIN



% Design Capability Utilization						
Average Flow/	Sep	Oct	Nov	Dec	Jan	Feb
	100%	105%	98%	98%	100%	101%

TC Energy

DESIGN CAPABILITY UTILIZATION
NORTH OF BENS LAKE – FLOW WITHIN





% Design Capability Utilization						
Average Flow/	Sep	Oct	Nov	Dec	Jan	Feb
	79%	90%	84%	91%	91%	90%

TC Energy

DESIGN CAPABILITY UTILIZATION
NORTH and EAST – FLOW WITHIN





% Design Capability Utilization						
Average Flow/	Sep	Oct	Nov	Dec	Jan	Feb
	76%	85%	83%	90%	90%	89%

TC Energy

FUTURE FIRM TRANSPORTATION SERVICE AVAILABILITY

Please consult with your Marketing Representative to discuss your Firm Transportation Service needs.

Estimated Firm Transportation Service Availability

Please refer to the following web site for current FT-R / FT-D Availability Maps:

http://www.tccustomerexpress.com/2801.html

HOW TO USE THIS REPORT

Overview

This report contains recent historical information on the level of utilization of firm transportation Service Agreements on the NGTL system, relative usage of interruptible service, level of utilization of design pipeline capacity.

Data is reported either by ***Pipeline Segment*** (25 segments make up the system) or ***Design Area*** (13 Design Areas for the system). Maps of both are included in the reference section.

Firm Transportation Service Contract Utilization

The Firm Transportation Service Contract Utilization report shows the percent utilization for each of the 25 NGTL pipeline segments and 3 major export delivery points comprising the total system. The utilization data is based on billed monthly volumes. Percent utilization is calculated as firm transportation service and firm transportation service + interruptible service divided by applicable receipt or delivery contract level. Historical Data involving billed volumes lags the current date by approximately two months.

Design Capability Utilization

The load factor/segment flow graphs show actual flow versus design capability values for various NGTL system areas. The graphs also show seasonal (winter/summer) design capability and average load factors (LF) for each season. Load factors are obtained by comparing the receipt, delivery, or throughput flow condition in each of the Alberta design areas against the corresponding design capability. Consequently, design capability utilization is measured as Average Actual Flow / Seasonal Design Capability. Data used in these reports lags the current date by at least one month.

Design Flow Capability utilization is a function of several factors that include:

- Total market demand for Alberta natural gas.
- Seasonal changes in market demand for Alberta natural gas.
- Receipt nominating practices of customers individually and in aggregate to meet that level of demand.
- Scheduled maintenance which could effect actual flow requirement in a design area at any given time.
- Design assumptions used in determining required segment flow requirement.

Future Firm Transportation Service Availability

The Future Firm Transportation Service Availability report presents guidelines and timing for all future firm transportation service requests.

NGTL Design Areas



(Last updated Oct 2019)

TC Energy

Last Updated April 2022



DEFINITION OF TERMS

Design Capability Utilization

Actual Flow
The amount of gas flowing within or out of the design area.

Design Capability
The volume of gas that can be transported from the design area on the pipeline system considering given design assumptions.

AVGLF (Average Load Factor)
The ratio between average *Actual Flow* and *Design Capability*. It is calculated for every design season (summer/winter) as shown on the graphs.

Intra NGTL System Deliveries
The amount of sales gas flowing off the system within an area.

Receipt Flow
Aggregate of actual receipts within an area and the *Actual Flow* of the upstream area.

Other

System Load Factor
The volume weighted average of the *Average Load Factor (AVGLF)* of all design areas on the system